

Tyres	Name	Size	Details	S12	S15	M18	L25	XL/50	XL75	XXL	3XL	4XL	5XL
	Pneumatic block profile	13	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed • 13cm width				●						
	Pneumatic block profile	15	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed			●	●	●					
	Pneumatic block profile non marking	16	• Hard surface like asphalt and concrete. • Indoor • Air or foamed • 10 cm width			●	●	●					
	Pneumatic block profile	16	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed • 10 cm width			●	●	●					
	Pneumatic block profile	16	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed • 16 cm width			●	●	●					
	Pneumatic block profile	18	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed • 18 cm width				●	●	●				
	Pneumatic block profile	18	• Hard surface like asphalt, concrete, pavement and hard lawn. • Indoor and outdoor • Air or foamed • 23 cm width			●	●	●	●				
	Pneumatic winter tyres	16	• Snow, rocky, sand and gravel surface • Indoor and outdoor • Air or foamed • 10 cm width			●	●	●					
	Pneumatic winter tyres	16	• Snow, rocky, sand and gravel surface • Indoor and outdoor • Air or foamed • 16 cm width			●	●	●					
	Pneumatic winter tyres	18	• Snow, rocky, sand and gravel surface • Indoor and outdoor • Air or foamed • 22 cm width			●	●	●	●				
	Pneumatic tractor tyres	16	• Sand, fields and gravel surface • Indoor and outdoor • Air or foamed • 16 cm width			●	●	●					
	Pneumatic tractor tyres	16	• Sand, fields and gravel surface • Indoor and outdoor • Air or foamed • 16 cm width			●	●	●	●				
	Pneumatic tractor tyres	18	• Sand, fields and gravel surface • Outdoor • Air or foamed • 25 cm width			●	●	●	●				
	Solid rubber tyres Continental SC10	10	• Normal profile • 4 inch rim • Super Elastic • 10 cm width	●	●								
	Solid rubber tyres Continental SC10 Non-marking	10	• Normal profile • 4 inch rim • Super Elastic • Clean, Non-marking • 10 cm width	●	●								
	Solid rubber tyres Continental K125/75-8/3.00 SC20	15	• Normal profile • 6 inch rim • Super Elastic • 12 cm width			●	●	●	●				
	Solid rubber tyres Continental K125/75-8/3.00 SC20 Non-Marking	15	• Normal profile • 6 inch rim • Super Elastic • Clean, Non-Marking • 12 cm width			●	●	●	●				
	Solid rubber tyres Continental K4.00-8/3.00 SC20	16	• Normal profile • 6 inch rim • Super Elastic • 10 cm width			●	●	●	●	●			
	Solid rubber tyres Continental K4.00-8/3.00 SC20 Non-Marking	16	• Normal profile • 6 inch rim • Super Elastic • Clean, Non-Marking • 10 cm width			●	●	●	●	●			
	Solid rubber tyres Continental	18	• Normal profile • Trelleborg XL • Super Elastic • 18 cm width							●	●		
	Solid rubber tyres Continental	18	• Normal profile • Super Elastic • SCE20 • Clean, Non-Marking • 18 cm width							●	●		
	Solid rubber tyres Continental	23	• Normal profile • Super Elastic • SCE20 • Optional Clean, Non-Marking • 170 mm width									●	
	Solid rubber tyres	29	• Normal profile • Super Elastic • SCE20 • Optional Clean, Non-Marking • 355 mm width										●
	Polyurethane tyres	29	• No profile • 6 inch rim • Cover can be renewed • 10 cm width						●				
	Beach tyres	18	• Beach profile • 8 inch rims • 25 cm width			●	●	●	●				
	Wheel cover	15	• Only for 15 inch tyres • 12 cm width					●	●	●			
	Wheel cover		• Only for 3XL, 4XL and 5XL								●	●	●
	Axle extension		• 10 - 20 cm more axle track • 10 cm more ground clearance						●				